



Patio Cover Comparison Chart

Feature / Patio Cover Type		Feria™ 	Sierra™ 	Tuscany™	Olympia™	Gala™	Joya™						
Product image													
Feature Images													
Basic Sizes		3 m Depth: 3.07 m Length 4.25 m Length 5.46 m Length 4 m Depth: 4.25 m Length	2.3 m Depth: 2.32 m Length 3 m Depth: 3.14 m Length 4.34 m Length 5.55 m Length	3 m Depth: 3.07 m Length 4.25 m Length 5.46 m Length 3 m Depth: 6.10 m Length 7.30 m Length 8.51 m Length 9.15 m Length 9.71 m Length	3 m Depth: 3.07 m Length 4.25 m Length 5.46 m Length 3 m Depth: 6.19 m Length 7.39 m Length 8.60 m Length 9.24 m Length 9.80 m Length	3 m Depth: 3.08 m Length 3 m Depth: 6.16 m Length 9.25 m Length	3 m Depth: 3.14 m Length 4.34 m Length 5.55 m Length 3 m Depth: 6.19 m Length 7.39 m Length 8.60 m Length 9.24 m Length 9.80 m Length						
Additional Sizes Available		3 m Depth: 6.10 m Length 7.30 m Length 8.51 m Length 9.15 m Length 9.71 m Length 4 m Depth: 6.06 m Length 7.87 m Length 8.50 m Length	2.3 m Depth: 4.64 m Length 6.96 m Length 3 m Depth: 6.19 m Length 7.39 m Length 8.60 m Length 9.24 m Length 9.80 m Length	3 m Depth: 6.10 m Length 7.30 m Length 8.51 m Length 9.15 m Length 9.71 m Length	3 m Depth: 6.19 m Length 7.39 m Length 8.60 m Length 9.24 m Length 9.80 m Length	3 m Depth: 6.16 m Length 9.25 m Length	3 m Depth: 6.19 m Length 7.39 m Length 8.60 m Length 9.24 m Length 9.80 m Length						
Roofing Type		8 mm multiwall polycarbonate panel		6 mm multiwall polycarbonate panel		16 mm multiwall polycarbonate panel		16 mm multiwall polycarbonate panel		8 mm multiwall polycarbonate panel			
Roofing Color Options & Light transmission		Clear panels - 65% Opal White panels - 25%		Clear - 80%		Clear - 80%		Clear - 61% Bronze - 10%		White - 32%		Clear - 65%	
Frame Color Options		White / Grey		White / Grey		White / Grey		White / Grey		White		White / Grey	
Structure / Glazing Options		White structure & Clear panels White structure & Opal White panels Grey structure & Clear panels		White structure & Clear panels Grey structure & Clear panels		White structure & Clear panels Grey structure & Clear panels Grey structure & Bronze panels		White structure & Clear panels White structure & Clear panels		White structure & Clear panels White structure & Clear panels		White structure & Clear panels Grey structure & Clear panels	
UV resistance		All UV resistant - 100% UV protected non yellowing panels & powder coated aluminum frame											
Weather resistance		Harsh weather resistant - Service temperature range: -40°C (-40°F) to 110°C (230°F)											
Frame		Heavy duty aluminum frame & galvanized steel connectors											
Poles		8 x 4 cm (3.15" x 1.6")		8 x 4 cm (3.15" x 1.6")		8 x 4 cm (3.15" x 1.6")		8 x 8 cm (3.15" x 3.15")		15 x 15 cm (5.9" X 5.9")		8 x 4 cm (3.15" x 1.6")	
Adjusting Range:	Wall Mounting Height	3 m Depth (10') From 260 to 305 H cm (102.3" - 120") 4 m Depth (13') From 260 to 305 H cm (102.3" - 120")		2.3 m Depth (7.5') From 257 to 283 H cm (101.2"-111.4") 3 m Depth (10') From 260 to 305 H cm (102.3" - 120")		3 m Depth (10') From 260 to 305 H cm (102.3" - 120")		3 m Depth (10') From 260 to 305 H cm (102.3" - 120")		3 m Depth (10') From 290 to 340 H cm (114.2" - 133.9")		3 m Depth (10') From 285 to 331 H cm (112.2" - 130.3")	
	Poles - Front to Back	3 m Depth (10') From 226 to 286 D cm (89" - 112.6") 4 m Depth (13') From 310 to 370 D cm (122" - 145.7")		2.3 m Depth (7.5') From 160 to 210 D cm (63" - 82.7") 3 m Depth (10') From 226 to 286 D cm (89" - 112.6")		3 m Depth (10') From 226 to 286 D cm (89" - 112.6")		3 m Depth (10') From 226 to 286 D cm (89" - 112.6")		3 m Depth (10') From 200 to 255 D cm (78.7" - 100.4")		-	
	Poles - Sideways	3 m Depth (10') From 0 to 54 cm (0" - 21.3") 4 m Depth (13') From 0 to 54 cm (0" - 21.3")		2.3 m Depth (7.5') From 5 to 54 cm (2" - 21.3") 3 m Depth (10') From 0 to 54 cm (0" - 21.3")		3 m Depth (10') From 0 to 54 cm (0" - 21.3")		3 m Depth (10') From 5 to 54 cm (2" - 21.3")		3 m Depth (10') From 10 to 55 cm (3.9" - 21.7")		3 m Depth (10') From 5 to 54 cm (2" - 21.3")	
Snow Load 		150 kg/m ² (30.7 lbs/ft ²)		120 kg/m ² (24.6 lbs/ft ²)		120 kg/m ² (24.6 lbs/ft ²)		150 kg/m ² (30.7 lbs/ft ²)		250 kg/m ² (52 lbs/ft ²)		150 kg/m ² (30.7 lbs/ft ²)	
Wind Resistance 		120 km/h - 75 mph		120 km/h - 75 mph		90 km/h - 56 mph		120 km/h - 75 mph		150 km/h - 93 mph		120 km/h - 75 mph	
Maintenance		Maintenance free, rinse with water											
Optional SideWall		✓		✓		✓		✓		-		-	
DIY Assembly		Click N' Lock roofing system Anchoring & foot-pads kit Screws, plugs & bolts included		Sliding panels roofing system Anchoring & foot-pads kit Screws, plugs & bolts included		Sliding panels roofing system Anchoring & foot-pads kit Screws, plugs & bolts included		Sliding panels roofing system Anchoring & foot-pads kit Screws, plugs & bolts included		Sliding panels roofing system Anchoring & foot-pads kit Screws, plugs & bolts included		Sliding panels roofing system Anchoring & foot-pads kit Screws, plugs & bolts included	
Eco-friendly - 100% recyclable & reusable													
Warranty													
Key Features		<ul style="list-style-type: none"> Durable rust resistant powder coated aluminum structure Virtually unbreakable panels are UV resistant & provide 100% protection from harmful UV rays Integrated gutter System with adjustable gutter heads A wide range of sizes available 		<ul style="list-style-type: none"> Durable rust resistant powder coated aluminum structure Virtually unbreakable panels are UV resistant & provide 100% protection from harmful UV rays Integrated gutter System with adjustable gutter heads 		<ul style="list-style-type: none"> Durable rust resistant powder coated aluminum structure Virtually unbreakable panels are UV resistant & provide 100% protection from harmful UV rays Integrated gutter System with adjustable gutter heads 		<ul style="list-style-type: none"> Sturdy & durable rust resistant powder coated aluminum structure Virtually unbreakable panels are UV resistant & provide 100% protection from harmful UV rays Integrated gutter System with adjustable gutter heads Extra thick polycarbonate panels 		<ul style="list-style-type: none"> Engineered to meet severe weather, heavy snow loads & high winds Robust, rust resistant powder coated aluminum structure Virtually unbreakable panels are UV resistant & provide 100% protection from harmful UV rays Integrated gutter system, compatible with standard downspouts Extra thick polycarbonate panels Robust Roman poles 		<ul style="list-style-type: none"> Elegant & aesthetic design Durable rust resistant powder coated aluminum structure Virtually unbreakable panels are UV resistant & provide 100% protection from harmful UV rays Integrated gutter System with adjustable gutter heads 	